













Icon Glossary

icon	description
 <p>ANSI A250.13-2003 windstorm resistant</p>	<p>ANSI A250.13-2003 Windstorm Resistant - Rating by the American National Standards Institute. Rates strength of product to withstand impact from flying objects with force of over 3,000 lbs. static force and 350 ft. lbs. impact force.</p>
 <p>fire rated</p>	<p>Fire Rated - Covers electric strikes used in fire door frame having ratings up to and including 3 hours. Includes both UL 10B “fire test” of door assemblies and UL10C “positive pressure fire test” of door assemblies.</p>
 <p>UL 1034 burglary listed</p>	<p>UL1034 Burglary Listed - Rating is achieved by passing tests at either 1500 lbs., 1000 lbs. or 500 lbs. static force and either 70 ft. lbs., 50 ft. lbs. or 33 ft. lbs impact force. Must also pass cycle testing at either 250,000 or 100,000 cycles. Product must display at what level of force it passed the UL1034 test at for consumer information.</p>
 <p>field selectable (12 or 24VDC)</p>	<p>Field Selectable 12/24 - Ability to select either 12 or 24 volt DC in the field. Strike comes configured as 12 volt.</p>
 <p>field selectable (fail secure / fail safe)</p>	<p>Field Selectable Fail Secure/ Fail Safe - Ability to select either fail secure or fail safe locking mode in the field. Strikes come configured for fail secure.</p>
 <p>grade 1</p>	<p>Grade 1 - Passed requirements of 1500 lbs. static force, 70 ft. lbs of impact force and withstands 500,000 cycles.</p>
 <p>grade 2</p>	<p>Grade 2 - Passed requirements of 1000 lbs. static force, 50 ft. lbs of impact force and withstands 300,000 cycles.</p>
 <p>cylindrical locksets</p>	<p>Cylindrical Locksets - A lock for a door prepared with one or more cross-bores and one or more edge-bores.</p>
 <p>mortise locks without deadbolts</p>	<p>Mortise Locks without Deadbolts - A lock case that fits into a prepared rectangular shaped recess in the edge or a door. Latchbolts are a spring actuated bolt, with a beveled surface, which, when aligned with the strike plate, engages it automatically.</p>
 <p>mortise locks with deadbolts</p>	<p>Mortise Locks with Deadbolts - A lock case that fits into a prepared rectangular shaped recess in the edge or a door. Deadbolts are bolts having no spring action operated by a thumb turn or key.</p>
 <p>rim exit devices</p>	<p>Rim Exit Devices - A latch mechanism which releases by depressing a cross bar or panel extending across the width of the door sometimes called a panic bar, panic exit hardware or fire exit bolt.</p>
 <p>specialty specialty locksets</p>	<p>Specialty Locksets - Includes specialty locksets including but not limited to: Cylindrical deadbolt, hook bolt, unit lock, weiser bolt, and narrow style aluminum lock.</p>